

SPEC SHEET

		AQUALIGHT	AQUAMAX
STYLE NO.		CDR5441AQSC	CDR7100AQSC
OUTER FABRIC	ARTICLE	CORDURA NYLON OXFORD 100%	CORDURA NYLON OXFORD 100%
	denier (WARP x WOOF)	160d x 195d	330d x 330d
	DENSITY (WARP x WOOF)	95 x 67 pcs/inch	48 x 65 pcs/inch
INNER FABRIC ARTICLE		NYLON 20d TRICOT 100%	NYLON 20d TRICOT 100%
STRUCTURE		4 Layer Fabric	4 Layer Fabric
		1.Face Fabric	1.Face Fabric
		2.Micro Porous PU Coating	2.Micro Porous PU Coating
		3.Non Porous PU Membrane	3.Non Porous PU Membrane
		4.Nylon Tricot (20 Denir)	4.Nylon Tricot (20 Denir)
SIZE (in x yd)		55 in x 53 yds	54 in x 52 yds
WEIGHT		235 g/sqm	288 g/sqm
Water Proof (W/P)		25.000 mmH ₂ O up	25.000 mmH ₂ O up
Water Repellency (initial / after 20 HL)		80 point or higher / 60 point	80 point or higher / 60 point
Moisture vapor Transmission		8.000 g/m ² /24hrs and more (B1)	8.000 g/m ² /24hrs and more (B1)